

ผังแสดงหัวสายไฟระบบหัวฉีด 3-4 สูบ ENERGY REFORM 2564

สีสายไฟอาจเปลี่ยนแปลงไปบ้าง ให้ตรวจจากหัวประกอบด้วย

WIRING HARNESS FOR PRIMIUM

COLOUR	DESCRIPTION	PIN	PIN	DESCRIPTION	COLOUR
Red	GAS INJECTOR C	28	56	GAS INJECTOR A	Yellow
Brown	GAS INJECTOR D	27	55	GAS INJECTOR B	Orange
		26	54		
		25	53		
		24	52		
		23	51		
Black	GROUND	22	50	GROUND	Black
Black	GAS INJECTORS POSITIVE A,B	21	49	GAS INJECTORS POSITIVE C,D	Black
		20	48	SWITCH COMM	Blue
Blue	GAS SOLENOID VALVES (F)	19	47	SERIAL COMM	Brown
Blue	GAS SOLENOID VALVES (R)	18	46		Red-black
		17	45	TX SERIAL	Pink
		16	44	SERIAL RX	White
Red-black	12V BATTERY	15	43		Red-black
COLOUR	DESCRIPTION	PIN	PIN	DESCRIPTION	COLOUR
		14	42		
		13	41	12 UNDER LOCK	Red-white
		12	40	REVOLUTIONS SIGNAL	Brown
		11	39	GAS PRESSURE	Orange-black
		10	38	EXTERNAL MAP/ABSOLUTE PRESSURE	Red-yellow
		9	37	WATER TEMPERATURE	Orange
		8	36	GAS TEMPERATURE	Orange-black
Yellow	CUT-OFF INJECTORS 4 INJECTORS SIDE	7	35	LEVEL SENSOR	White
Yellow-black	CUT-OFF INJECTORS 4 CPU SIDE	6	34	SUPPLY LEVEL SENSOR	Green
Green	CUT-OFF INJECTORS 3 INJECTORS SIDE	5	33	OUT LAMBDA 1	Grey
Green-black	CUT-OFF INJECTORS 3 CPU SIDE	4	32	IN LAMBDA 1	Purple
Red	CUT-OFF INJECTORS 2 INJECTORS SIDE	3	31	OUT LAMBDA 2	Grey-black
Red-black	CUT-OFF INJECTORS 2 CPU SIDE	2	30	IN LAMBDA 2	Purple-black
Blue	CUT-OFF INJECTORS 1 INJECTORS SIDE	1	29	CUT-OFF INJECTORS 1 CPU SIDE	Blue-black